



SE220HSZ (English Units)

High-Speed All-Electric

CLAMP SPECIFICATIONS

Clamping force	U.S. ton	242
Distance between tie-bars	in	24.02 x 22.05
Overall size of platens (H x V)	in	34.65 x 32.68
Open daylight (max.)	in	44.49
Mold space (min.-max.)	in	11.81 – 22.83
Opening stroke (max.)	in	21.65
Mold open/close speed (max.)	in/sec	51.18
Locating ring diameter	in	4.0
Ejector pattern		Center, 7.0 in, 16.0 in (13 points)
Ejector stroke	in	5.91
Ejector force	U.S. ton	6.61

INJECTION SPECIFICATIONS

Plasticizing unit	C560M							C900L				
Screw diameter	mm	28	32	36	40	45	50	45	50	56		
Injection pressure	p.s.i.	42,185	40,183	39,611	40,040	31,460	25,454	38,830	31,434	25,033		
Holding pressure	p.s.i	42,185	40,183	39,611	32,032	25,168	20,363	38,830	25,003	19,913		
Injection capacity	in ³	5.2	7.9	9.9	12.2	15.5	19.2	20.1	24.8	31.1		
Injection weight (GPPS)	g	83	124	156	193	244	302	316	390	489		
	oz	2.9	4.4	5.5	6.8	8.7	10.7	11.2	13.8	17.3		
Plasticizing capacity (max.)	lb/hr	82	117	168	223	300	425	328	445	542		
Screw speed (max.)	rpm	400							360			
Temperature control zones		5						6				
Heater capacity	KW	6.6	7.6	8.5	10.4	11.1	11.3	23.3	26.8	31.2		
Injection rate (max.)	in ³ /sec	13.2	17.1	21.7	26.9	34.0	41.9	34.0	41.9	52.6		
Injection speed (max.)	in/sec	13.8										
Screw stroke	in	5.51	6.30						8.15			
Nozzle contact force	U.S. ton	6.61										
Inj. unit stroke (penetration)	in	16.93 (2.56)						17.72 (2.56)				
Hopper capacity	in ³	3051						6102				

MACHINE SPECIFICATIONS

Main breaker capacity	amps	225 @ 230V
Dimensions (L x W x H)	in	253 x 62 x 81
Machine weight	U.S. ton	11.1
		12.0

NOTE: Specifications subject to change without notice. Machine series photo at top may be different model size.