



SE280HSZ (English Units)

High-Speed All-Electric

CLAMP SPECIFICATIONS

Clamping force	U.S. ton	308
Distance between tie-bars	in	26.97 x 25.00
Overall size of platens (H x V)	in	37.40 x 34.84
Open daylight (max.)	in	48.03
Mold space (min.-max.)	in	13.78 – 24.41
Opening stroke (max.)	in	23.62
Mold open/close speed (max.)	in/sec	51.18
Locating ring diameter	in	4.0
Ejector pattern		Center, 7.0 in, 16.0 in (13 points)
Ejector stroke	in	5.91
Ejector force	U.S. ton	6.61

INJECTION SPECIFICATIONS

Plasticizing unit		C900L			C1250L		
		45	50	56	50	56	63
Screw diameter	mm	38,830	31,434	25,033	39,825	31,718	25,033
Injection pressure	p.s.i.	31,007	25,033	19,913	31,860	25,318	19,913
Holding pressure	p.s.i.	20.1	24.8	31.1	27.3	34.3	43.4
Injection capacity	in ³	g	316	390	489	430	539
		oz	11.2	13.8	17.3	15.2	19.1
Injection weight (GPPS)		lb/hr	328	445	542	445	542
Plasticizing capacity (max.)		rpm	400	400	360	400	360
Screw speed (max.)		KW	23.3	26.8	31.2	26.8	31.2
Heater capacity (6 zones)		in ³ /sec	34.0	41.9	52.6	41.9	52.6
Injection rate (max.)		in/sec			13.8		
Injection speed (max.)		in		8.15		8.98	
Screw stroke		U.S. ton		6.61		6.61	
Nozzle contact force		in		17.72 (2.56)		17.72 (2.56)	
Injection unit stroke (penetration)		in ³		6102		6102	
Hopper capacity							

MACHINE SPECIFICATIONS

Main breaker capacity	amps	225 @ 230V	
Machine dimensions (L x W x H)	in	284 x 66 x 89	
Machine weight	U.S. ton	14.3	15.1

NOTE: Specifications subject to change without notice. Machine series photo at top may be different model size.