



# SE350EV-A<sup>HD</sup> (English Units)

High-Duty Mid-Sized All-Electric



## CLAMP SPECIFICATIONS

[www.sumitomo-shi-demag.us](http://www.sumitomo-shi-demag.us)

Clamping force	U.S. tons	393
Distance between tie-bars	in	32.68 x 32.68
Overall size of platens (H x V)	in	44.88 x 44.88
Open daylight max. - standard	in	56.10
- With opt. 100 mm extension		60.04
- With opt. 200 mm extension		63.98
Mold space min. - max.	in	13.78 – 27.56
- With opt. 100 mm extension		13.78 – 31.50
- With opt. 200 mm extension		13.78 – 35.43
Mold opening stroke max.	in	28.54
Mold open/close speed max.	in/s	52.99
Locating ring diameter	in	4.0
Ejector pattern		Center (13 points)
Ejector force (with opt. added force)	U.S. tons	6.74 (11.24)
Ejector speed max.	in/s	10.51
Ejector stroke	in	8.66
Mold loading max. (moving side)	lbs	11,464 (7606)

## INJECTION SPECIFICATIONS

Plasticizing unit		C1100HD			C1600HD			C2200HD		
		50	56	63	56	63	71	63	71	80
Screw diameter	mm	50	56	63	56	63	71	63	71	80
Injection pressure max.	p.s.i.	33,359	27,122	21,466	33,359	27,267	21,466	31,328	27,267	21,466
Holding pressure max.	p.s.i.	33,359	27,122	21,466	33,359	27,267	21,466	31,328	27,267	21,466
Injection capacity	in <sup>3</sup>	31.1	39.1	49.4	43.6	55.2	70.1	60.8	77.3	98.1
Injection weight (GPPS)	g	490	614	778	685	867	1102	957	1216	1544
	oz	17.3	21.7	27.4	24.2	30.6	38.9	33.8	42.9	54.5
Plasticizing capacity max.	lb/hr	333	423	500	423	500	507	500	507	668
Injection rate max. (opt. high-velocity filling)	in <sup>3</sup> /s	19.2 (33.5)	24.0 (42.0)	30.4 (53.2)	24.0 (42.0)	30.4 (53.2)	38.6 (67.6)	30.4 (53.2)	38.6 (67.6)	49.1 (85.9)
Screw stroke	in	10.2			11.4			12.6		
Injection speed max. (opt. high-velocity filling)	in/s	6.3 (11.0)								
Screw speed max.	rpm	250					200	250	200	
Number of temperature control zones		6								
Heater capacity	kW	19.2	21.1	28.4	21.1	28.4	30.5	28.4	30.5	34.6
Nozzle contact force	U.S. tons	6.52								
Injection unit stroke (penetration)	in	17.72 (2.56)								
Hopper capacity	in <sup>3</sup>	6102								

## MACHINE SPECIFICATIONS

Main breaker capacity	amps	225 @ 230 V
Machine dimensions (L x W x H)	in	293 x 82 x 85
Machine weight	U.S. tons	18.2

NOTE: Specifications subject to change without notice. Machine series photo at top may be different model size.